# FC SERIES OUTDOOR STANDARD LED PRODUCTS



MODEL NO.: FC1600D

**OUTDOOR FIXED LED DISPLAY** 

**DIP OUTDOOR FRONT & BACK SERVICE** 

STANDARDIZED CABINET SIZE 960X960MM

**SEEMLESS CONNECTION** 

DIE-CASTING ALUMINUM CABINET MATERIAL





**ENERGY SAVING** 



HIGH CONTRAST RATIO



HIGH BRIGHTNESS



**EASY MAINTENANCE** 




IP 65 WATER PROOF



HIGH-DEFINITION DISPLAY



#### 960X960mm








	ITEMS	PARAMETERS
Physical Parameters	LED Configuration	DIP346
	Pixel Pitch ( mm)	16
	Module Resolution(dots)	20X20
	Panel Resolution (dots)	60X60
	Pixel Density (dots/m²)	3,906
	Module Size (WxHxD) /( mm)	320x320
	Panel Dimension (WxHxD) /(mm)	960x960
	Panel Material	Die Casting Aluminum
	Panel Module Composition(W xH)	3x3
	Panel Weight (Per/pcs)	38
	Module Weight( Per/kg)	2
Optical Processing	Color processing (Bit)	16
	Grey Level	65536
	Refresh Rate (Hz)	≥1920
	Driving Mode(scan)	Constant Static
	Brightness ( nit )	9000
	Viewing Angle (H/V)	110/45
Electrical Parameters	Input Voltage (V)	AC110/220V±10%
	Input Power Frequency (Hz)	50/60
	Max Power (W/m²)	547
	Average Power ( W/m²)	182
Operating Environment	Storage Temperature (°C )	From-10 to 50
	Operating Temperature (℃)	From-20 to 60
	Storage Humidity(RH)	10%~90%
	Operating Humidity (RH)	10%~90%
	IP Rating	IP65/IP54
	Lifetime (hrs)	100000
	Usage Environment	Outdoor fixed installation
	Panel Maintenance Method	Front/Rear Maintenance
Quality warranty	FC CE	Intertek CO


## PRODUCT DESCRIPTION






## **Fast And Easy Maintenance**









Step 1: Use "T" Wrench and insert one hole of the module

then rotate "T" wrench in anti-clockwise direction to unlock.


Step 2: Repeat step 1 on the other hole to release the


module separate from cabinet easily.

Step 3: Disconnect power & data cable.










Two optional mask caps designed special for outdoor LED advertising, and tested for a better visual experience with maximum brightness and high contrast ratio.



#### Innovated Seemless Connection








High precision and integral structure, flexibly fast locking function, used die casting aluminum cabinet material with no gap assembly.

FC series products comply with high IP rating that ensure all component can be able to operate even in extreme environment conditions.

## APPLICATIONS






Gaming & Lottery Advertising



Cinima Leisure time



Customized Outdoor Advertising Project



Stadium Project in South Africa



For Sales & New Arrivals Advertising



Lifestyle & News in Outdoor Display

### SHENZHEN NEWSTAR OPTOELECTRONICS CO., LTD





info@newstar-led.com



