





Shenzhen Newstar Optoelectronics Co., Ltd.

Address: No.10, Kukeng 2 Road, Tongfuyu Industrial Zone, Kukeng Community, Guanlan Street, Longhua District, Shenzhen City,China.

FC660 module Product Parameters		
Photo	LED Module	LED Module
		
	ITEMS	PARAMETERS
Physical Parameters	LED Configuration	SMD2727
	Pixel Pitch (mm)	6.67mm
	Module Resolution(dots)	48x48
	Pixel Density (dots /m ²)	22,477
	Module Size (W x H x D) /(mm)	320x320mm
	Module Weight(Per/kg)	1Kg
Optical Processing	Color processing (Bit)	16
	Grey Level	65536
	Refresh Rate (Hz)	≥1920
	Driving Mode(scan)	1/4
	Brightness (nit)	6500nit
	Viewing Angle (H/V)	140/140
Electrical Parameters	Input Voltage (V)	AC110/220V±10%
	Input Power Frequency (Hz)	50/60
	Max Power (W/pcs)	85
	Average Power (W/pcs)	28
Operating Environment	Storage Temperature (°C)	From -10 to 50
	Operating Temperature (°C)	From 0 to 40
	Storage Humidity (RH)	10%~90%
	Operating Humidity (RH)	10%~90%
	IP Rating	IP65/IP54
	Lifetime (hrs)	100000
	Usage Environment	outdoor fixed installation
	Maintenance Method	Front/Rear Maintenance
Certification	CE/ RoHS/CCC/UL/	