










Shenzhen Newstar Optoelectronics Co., Ltd.

Address: No.10, Kukeng 2 Road, Tongfuyu Industrial Zone, Kukeng Community, Guanlan Street, Longhua District, Shenzhen City,China.

| F11010D module Product Parameters | | |
|-----------------------------------|---|--|
| Photo | LED Module | LED Module |
| |  |  |
| | ITEMS | PARAMETERS |
| Physical Parameters | LED Configuration | DIP346 |
| | Pixel Pitch (mm) | 10.16mm |
| | Module Resolution(dots) | 30x30 |
| | Pixel Density (dots /m ²) | 9,604 |
| | Module Size (W x H x D) /(mm) | 1'x1'(304.8mmx304.8mm) |
| | Module Weight(Per/kg) | 1Kg |
| Optical Processing | Color processing (Bit) | 16 |
| | Grey Level | 65536 |
| | Refresh Rate (Hz) | ≥1920 |
| | Driving Mode(scan) | 1/3 |
| | Brightness (nit) | 10000nit |
| | Viewing Angle (H/V) | 120°/65° |
| Electrical Parameters | Input Voltage (V) | AC110/220V±10% |
| | Input Power Frequency (Hz) | 50/60 |
| | Max Power (W/pcs) | 36 |
| | Average Power (W/pcs) | 12 |
| Operating Environment | Storage Temperature (°C) | From -10 to 50 |
| | Operating Temperature (°C) | From 0 to 40 |
| | Storage Humidity (RH) | 10%~90% |
| | Operating Humidity (RH) | 10%~90% |
| | IP Rating | IP65/IP54 |
| | Lifetime (hrs) | 100000 |
| | Usage Environment | outdoor fixed installation |
| | Maintenance Method | Front/Rear Maintenance |
| Certification | CE/ RoHS/CCC/UL/ |      |