





Shenzhen Newstar Optoelectronics Co., Ltd.

Address: No.10, Kukeng 2 Road, Tongfuyu Industrial Zone, Kukeng Community, Guanlan Street, Longhua District, Shenzhen City,China.

FN480 module Product Parameters		
Photo	LED Module	LED Module
		
	ITEMS	PARAMETERS
Physical Parameters	LED Configuration	SMD1921
	Pixel Pitch (mm)	4.81mm
	Module Resolution(dots)	52x52
	Pixel Density (dots /m ²)	43,264
	Module Size (W x H x D) /(mm)	250x250mm
	Module Weight(Per/kg)	1Kg
Optical Processing	Color processing (Bit)	16
	Grey Level	65536
	Refresh Rate (Hz)	≥1920
	Driving Mode(scan)	1/9
	Brightness (nit)	6500nit
	Viewing Angle (H/V)	140/140
Electrical Parameters	Input Voltage (V)	AC110/220V±10%
	Input Power Frequency (Hz)	50/60
	Max Power (W/pcs)	58
	Average Power (W/pcs)	19
Operating Environment	Storage Temperature (°C)	From -10 to 50
	Operating Temperature (°C)	From 0 to 40
	Storage Humidity (RH)	10%~90%
	Operating Humidity (RH)	10%~90%
	IP Rating	IP65/IP54
	Lifetime (hrs)	100000
	Usage Environment	outdoor fixed installation
	Maintenance Method	Front/Rear Maintenance
Certification	CE/ RoHS/CCC/UL/	